



MP-A40
SEIKO Thermal line dot printer



Reliable



Easy paper operation



**Wide variety of
driver and SDK**

- **High Reliability**
- **Drop rating: 2.0m(6.6feet) multiple**
- **IP rating: IP54**
- **Operating temperature: -20°C to 50°C**
- **Wide variety of driver and SDK for mobile equipment**
- **Compact and light weight**
- **Easy paper operation**
- **Wide variety of driver and utility software suite**

MP-A40 printer specification

Model	MP-A40
Method	Seiko Thermal line dot printing
Number of dots/line	832
Resolution (dots/mm)	8
Paper width (mm)	80 ⁺⁰ ₋₁ / 100 ⁺⁰ ₋₁ / 105 ⁺⁰ ₋₁ / 112 ⁺⁰ ₋₁
Printing width (mm)	104
Speed (mm/sec) max	105
Outside diameter of paper roll (mm) max	58
Character matrix (HxW mm)	24 x 12, 24 x 24, 16 x 8, 16 x 16
Character dimensions (HxW mm)	3.0 x 1.5, 3.0 x 3.0, 2.0 x 1.0, 2.0 x 2.0
Type of Paper	Roll paper, Label roll paper
Character type	Code page : 17pages, Katakana character, Option font, Downloaded character, User-defined character, JIS 1 & 2 level kanji
Bar code	UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128,PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar
Power supply(v)	Option : Specified AC adapter, Li-Ion battery
Communication interface	USB, Bluetooth®, WLAN
Input buffer	4K bytes
Command	ESC/POS™ conformity, CPCL conformity, Markup Language
Cutting	Tea bar
Drop Rating	2.0m (6.6feet) multiple
IP rating	IP54
Operating temperature (°C)	-20 to 50
Service life (km)	50
Dimensions (WxDxH mm)	156 x 152 x 71
Mass (g)	Approx. 760
Standard	FCC, CE, VCCI
Option	AC adapter, Battery pack, Battery charger (single/quadruple), AC cable, USB cable, Serial cable, Car charger, Strap
Software	Printer driver, Windows® CE(SDK), Android™(SDK), iOS

Hong Kong

Flat D, 5/F Excelsior Building,364 Nathan Road,Kowloon, Hong Kong

+852 2376 2803
sales@glorystargroup.com

PRC

Bldg 9, 4/F Zhong Yuntai Technology Industrial Park, Tangtuo No.1 Road, Shiyan Street, Baoan, ShenZhen, PRC

+86 755 2600 1808
sales@glorystargroup.com

United States

Representatives
California, New York,USA

+626 228 5927
sales@glorystargroup.com