





GLORYSTAR

Ultron Windows Touchscreen Computer i5



Capacitive Touch



Windows



Durable Built to Last

Overview

The ULTRON Windows Touchscreen Computer is a cutting-edge, all-in-one touchscreen solution designed for commercial and industrial applications, available in 10-inch, 15.6-inch, and 21.5-inch models to power self-service kiosks, restaurant ordering kiosks, digital signage displays, and more. Equipped with Intel® i5-1235U processors, this touchscreen computer supports Windows 11 and Linux, delivering robust performance for retail touchscreen solutions, healthcare kiosks, and education kiosks. Its high-brightness display with optically bonded touchscreen glass ensures vibrant visuals, while robust connectivity (USB 3.0/3.2, dual RJ45 Ethernet, Wi-Fi 6, and optional 4G LTE) and versatile VESA mounting options make it ideal for customizable kiosks, interactive displays, and point-of-sale kiosks in hospitality and retail environments.

Available in 10.1", 15.6" and 21.5" widescreen.

Easy deployments with various VESA mounting.

15.6" and 21.5" with anti-glare glass and optical bonding capacitive touch panel technology.

Specification

Processors	I5- 1235U				
Model Number		ULT101 Part#1235U		ULT156 Part#1235U	ULT215 Part#1235U
Screen Size		10"		15.6"	21.5"
Panel Info	Resolution	1280 x 800		1920 x 1080	1920 x 1080
	Panel Brightness	500cd/m²		450cd/m²	450cd/m²
	Brightness	425cd/m² with touch Screen		400cd/m² with touch Screen	400cd/m² with touch Screen
	Contrast Ratio	800:1		1000:1	1300:1
	Aspect Ratio	16:10		16:9	16:9
	Active Display Area	216.96x135.6mm		344.16 × 193.59 mm	476.064 x 267.786mm
	Response time	10ms		20ms	14ms
	Viewing Angle	85°/85°/85°/85		89°/89°/89°/89°	89°/89°/89°/89°
Touch Data	Touch Tech	G+G 10 point cap touch		G+G 10 point cap touch Anti-glare glass	
	Hardness Of Surface	10inch: > 6H 15.6inch: ≥ 7H 21.5inch: > 6H			
	Touch method	Finger touch 、 Capacitive stylus			
	Transparency	10.1inch and 21.5inch : ≥86% 15.6inch: ≥85%			
	Glass Thickness	2mm (Not including Sensor thickness)			
	Bonded Panel	15.6inch -21.5inch : Support Optical bonded capacitive touch Panel 10inch : Not supported Bonded Panel			
CPU & System	CPU	i5-1235U			
	P-core Max Turbo Frequency	4.4GHz			
	E-core Max Turbo Frequency	3.3GHz			
	core	10			
	Thread	12			
	CPU Cache	12MB			
	BIOS	AMI UEFI BIOS			
RAM	RAM	8GB , Dual Channel SO-DIMM DDR4 (Max 64GB)			
ROM	Storages	256GB, M.2 for NVME 2280 SSD			
Software	OS	Windows 11 64 bit, Linux 64 bit			
Display	GPU Chipset	Intel Iris® Xe Graphics eligible/UHD Graphics depends on CPU			
	Displayport	N/A			
Audio	Speaker	2W x 2			
Ethernet	Connector	2 x RJ45			
	Wake on Lan	Yes			
	WIFI/ Bluetooth	IEEE 802.11a/b/g/n/ac/ax(PreStandard) , Bluetooth 5.0 (Dual antenna)			
Storage	Slot	M.2 for NVME 2280 SSD			
General	Material & Color	Metal Housing with Black Matte Paint			
	Camera	2 MP			
	4G(Optional)	4G and WIFI function Choose one of the two			
	Metal Button	1×Power button; 1×Reset button (1×Power button for 10 inch)			
Rear Panel I/O	USB	4xUSB 3.2			
	Audio	Line-out x 1, Mic-in x 1			
	LAN	1 x (1000Mbps) ; 1 x (2500Mbps)			
	VGA	N/A			
Insider PCBA	M.2	1×for NVME 2280 SSD			
	SATA3.0	1			
	COM	6 x RS232(default) or 5*RS232+1*RS485(COM1)			
	USB 2.0	4 x USB2.0 header			
	I/O	8 x GPIO			
Hardware Monitor	Hardware Monitor	CPU system temperature; onboard voltage; Watchdog; and auto power on			
	Included in Box	Ultron tablet, Power Adaptor, Power cable			
	Operating Environment	Working Temperature: 0-45 degree celsius			
	Language	Multi language			
Power Management	Power supply unit	External	External		External
	Power supply	12V 7.5A	DC 12V 7.5A		DC 12V 7.5A
	Power usage	TBD	55W typical, 1.3W stand by, 1.3W off mode		TBD
Sustainability	Regulations	FCC, CE, RoHS support			
	REACH SVHC	REACH does not contain SVHC above 0.1%: Lead			
Mounting	VESA	VESA75 for 10inch, VESA 100 for 15.6 and 21.5 inch			
Dimensions	Size (WxDxH)	10 inch: TBD	15.6 inch: 376.47 x 228.47 x 42.8mm	21.5 inch: 515.87 x 311.87 x 42.8mm	
	Product Weight	TBD	2.9kg	4.9kg	
	Gift Box Size	10 inch: TBD	15.6inch: 443 x 115 x 303 mm	21.5inch: 583 x 115 x 382mm	
	Master Carton Size	10 inch: TBD	15.6inch: 464 x 365 x 327mm	21.5inch: 604 x 248 x 406mm	
	Master Carton Weight	10 inch: TBD	15.6 inch: 12.3Kg	21.5 inch: 15.3Kg	
	Units per Master Carton	10 inch: TBD	15.6inch: 3pcs	21.5inch: 2 pcs	

Peripheral Options

1D Barcode Newland	BC100-NEW
2D Barcode Zebra	BC200-ZEB
Elatec RFID Reader Metal Housing	NEBA1703 PART#E002
Windows11 IoT Enterprise LTSC	ULT Part# WIN KEY
4G (LTE) Module	JAF-009

Mounting Options

Wall Mount	WM015012S
Desk Mount	FIX-027 (Foldable base bracket)
	FIX-028 (Adjustable Desk Mount)
	FIX-030 (Foldable base bracket)

CONTACT US

United States	Hong Kong	ShenZhen
101 Hudson St., 21st Floor Jersey City, NJ 07302 626 228 5927	Flat D, 5/F, Excelsior Building, 364 Nathan Road, Kowloon, Hong Kong 852 23762803	Bldg. 9, 4/F Zhong Yuntai Technology Industrial Park, Tangtou No.1 Road, Shiyan Street, Baoan, ShenZhen, PRC 86 755 2600 1808

To find out more about our extensive range of Glor Star solutions, go to www.glorystargroup.com , or call the office nearest you. For more information, please contact us at sales@glorystargroup.com. Glory Star reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Glory Star, the Glory Star logo, STAR CONTROL and STAROS are either trademarks or registered trademarks of Glory StarGroup Limited. All other trademarks are the property of their respective owners.