



GLORYSTAR


MAGNETAR Weatherproof Touch Screen



IP65 Front Glass



1000 nits brightness



Fingerprint & Scratch Resistant

Overview

The Glory Star Magnetar Weatherproof Touch Screen is IP65 rated, dust and water resistant in the front glass. Equipped with a high brightness screen, fingerprint and scratch resistance surface makes it a true industrial grade solution. It is cost effective for system integrators who require a reliable product for indoor and outdoor applications.

Designed with reliability from the start, Glory Star's Magnetar weatherproof touch screen delivers seamless and accurate touch response with a 6H scratch resistant touch glass, that is enough to withstand demanding applications, making these products very suitable for use in public environments.

Processors		J6412		
Model Number		MAG101 Part#J6412	MAG156 Part#J6412	MAG215 Part#J6412
Screen Size		10"	15.6"	21.5"
Panel Info	Resolution	1280x 800	1920 x 1080	1920 x 1080
	Brightness	1000cd/m2		
	Contrast Ratio	1300:1	1000:1	5000:1
	Aspect Ratio	16:10	16:9	16:9
	Active Display Area	216.96 x 135.6mm	344.16 x 193.59mm	476.64x268.11mm
	Viewing Angle	85°/85°/85°/85°	89°/89°/89°/89°	89°/89°/89°/89°
	Response time	25ms	25ms	25ms
Touch Data	Impact Rating	IK07		
	Touch Tech	G+G Capacitive Touch 10pt IP65 Rating Optical bonded capacitive touch (touch on water or latex glove) UV Protection		
	Hardness Of Surface	≥ 6H	> 6H	> 6H
	Touch method	Finger touch 、 Capacitive stylus		
	Transparency	≥85%	≥86%	≥86%
	Touch Glass Thickness	2.75mm	2.7mm	2.7mm
	Response Time	10ms	≤ 35ms	≤ 35ms
	Bonded Panel	Yes		
CPU& System	CPU	J6412		
	CPU Turbo Boost	2.6GHz		
	Base Frequency	2.0GHz		
	CPU Cache	1.5MB		
	BIOS	AMI UEFI BIOS		
RAM	RAM	8GB , Single Channel SO-DIMM DDR4 (Max 32GB)		
ROM	Storages	For 10 inch M.2 - 2280 256GB SSD For 15 and 21 inch SATA3.0 256GB SSD		
Software	OS	Window 10 IoT Enterprise LTSC 2019 english version 64 bit), Linux 32 / 64 bit		
Display	GPU Chipset	Intel® UHD Graphics for 10th Gen		
	Display Port	DP 1.4		
Audio	Speaker	2WX 2		
Ethernet	Controller	10/100/1000Mbps		
	Connector	2 x RJ45		
	Wake on Lan	Yes		
Storage	WiFi/ Bluetooth Slot	IEEE 802.11a/b/n/ac, Wi-Fi compliant , Bluetooth 4.0 For 10 inch : 1x M.2 for 2280 SSD For 15 and 21 inch : 1x SATA3.0		
	Housing	Material & Color	Metal Outdoor Housing with Black Matte Paint	
Rear Panel I/O	Chassis	IP65 front IPX2 rear		
	Front	IP65		
	Back	IPX2		
Insider PCBA	USB 3.2	4xUSB 3.2		
	Audio	Line-out x 1; Mic-in x 1		
	LAN	2(10/100/1000Mbps)		
Power	COM	5 x RS232 / 1 x RS485 (inside PCBA)		
	USB 2.0	3 x USB2.0 header (inside PCBA)		
	I/O	Programmable 8 x GPIO (inside PCBA)		
Hardware Monitor	Standard Port	1 x 12V DC-IN		
	Sensor	Voltage sensor; Watchdog; Plug and Start		
	Included in Box	MAGNETAR tablet, Power Adaptor, Power cable,Adjustable mounting brackets		
	Operating Environment	-10°C—60°C		
Power Management	Language	Multi language		
	Power supply unit	External	External	External
	Power supply	12V 5A	12V 5A	12V 5A
Sustainability	Power usage			
	Regulations	RoHS support		
	REACH SVHC	REACH does not contain SVHC above 0.1%: Lead		
Mounting	VESA	VESA 100		
Power Adaptor	Input	AC 100-240V, 50/60Hz		
Dimensions	Size (WxDxH)	10 inch: 278.56×197.2×40.8mm	15.6 inch: 389.45×238.74×45.8mm	21.5 inch: 523.9×315.4×46.3mm
	Product Weight	2.5 kg	4.5 kg	6.7 kg
	Gift Box Size	10 inch : 396 x 241 x 86 mm	15.6inch: 443 x 115 x 303 mm	21.5inch: 583 x 115 x 382mm
	Master Carton Size	10 inch : 506x 410 x 288mm	15.6inch: 464 x 365 x 327mm	21.5inch: 604 x 248 x 406mm
	Master Carton Weight	10 inch: 17.6kg 15.6 inch: 15kg 21.5 inch: 15.2kg		
	Units per Master Carton	10 inch: 6pcs 15.6inch: 3pcs 21.5inch: 2 pcs		

Accessories

Adjustable mounting brackets	10" Side Bracket X 2 (included in the package) 15.6" - 21.5" Side Bracket X 4 (included in the package)
------------------------------	--

Mounting Options

Wall Mount	WM015012S
Desk Mount	FIX-027 (Foldable base bracket) (for 15.6", 21.5" models)
	FIX-028 (Adjustable Desk Mount) (for 10", 15.6" models)
	FIX-030 (Foldable base bracket) (for 15.6", 21.5" models)

CONTACT US

United States	Hong Kong	ShenZhen
101 Hudson St., 21st Floor Jersey City, NJ 07302 626 228 5927	Flat D, 5/F, Excelsior Building, 364 Nathan Road, Kowloon, Hong Kong 852 23762803	Bldg. 9, 4/F Zhong Yuntai Technology Industrial Park, Tangtou No.1 Road, Shiyan Street, Baoan, ShenZhen, PRC 86 755 2600 1808

To find out more about our extensive range of Glor Star solutions, go to www.glorystargroup.com, or call the office nearest you. For more information, please contact us at sales@glorystargroup.com. Glory Star reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Glory Star, the Glory Star logo, STAR CONTROL and STAROS are either trademarks or registered trademarks of Glory Star Group Limited. All other trademarks are the property of their respective owners.